

CALCE																	
CARRARA																	
Description	<p>The exclusive line CALCE, is characterized by elegance and purity. A special, completely natural mineral system that respects the environment and gives wellness to your rooms.</p> <p>Perfectly balanced formulas that guarantees elasticity, durability and workability never seen before, at any thickness.</p> <p>The use of the new decorative lime system in homes is synonymous with well-being, the high breathability will allow the walls to breathe avoiding the formation of moisture and its hygienizing nature it will significantly reduce the formation of condensation and mold. of classic, European masonry.</p>																
Uses	Universal use on plaster of all types: gypsum-based, containing lime, fiber-cement, etc, on plasterboard and wood surfaces.																
Surface preparation	<p><u>New surfaces</u> Make sure the surface is totally dry and having at least 30 days. Clean from dust and dirt. Pre-fill any depressions and smooth the surface. Apply a coat of Solerosso - acrylic primer diluted up to 300% and let it dry for 12 hours.</p> <p><u>Previously painted surfaces</u> Clean from dust, dirt, old paints that tends to peel and salt efflorescence. Fill any irregularities and/or imperfections and smooth the surface. Clear up the surface from alga, mould it with Bioattiva solution and let it dry for at least 24 hours. Apply a coat of Solerosso - acrylic primer diluted up to 300% and let it dry for 12 hours.</p>																
Application	<p><u>Base:</u> After sanding, clean the excess powder and leveled from every imperfection the support, apply, by roller or brush, a coat of BASE R coloured with Italyamix Colouring System. Allow it to dry for at least 8 hours.</p> <p><u>Finish:</u> Apply a coat of CALCE evenly with a steel trowel, avoiding to leave ripples and ridges. Perform the desired effect with specific accessories, choosing from: Cementina, Carrara, Rigato, Rioma, Torino, Carrara Marmo, Stucco Crack, Carrara Fusion.</p> <p>Before the product dries, smooth carefully with the steel trowel. Leave to dry for at least 12 hours.</p>																
Technical Data	<table border="0"> <tr> <td style="text-align: right;">Color</td> <td>White + Color samples</td> </tr> <tr> <td style="text-align: right;">Appearance</td> <td>Creamy</td> </tr> <tr> <td style="text-align: right;">Packaging</td> <td>BASE R: 4L-2,5L-0,750L CARRARA: 20KG-5KG GALLIPOLI FINO: 1,25KG PORTOFINO FINO: 1,25KG NAPOLI LUX: 1KG</td> </tr> <tr> <td style="text-align: right;">Vehicle type</td> <td>Vinyl acetate / vinyl-versed</td> </tr> <tr> <td style="text-align: right;">Yield</td> <td>BASE R: 6-8 sqm/Kg CARRARA: 2-2,5 sqm/Kg GALLIPOLI FINO: 10 sqm/Kg PORTOFINO FINO: 10 sqm/Kg NAPOLI LUX: 10 sqm/Kg</td> </tr> <tr> <td style="text-align: right;">ph</td> <td>8 +/- 0,5</td> </tr> <tr> <td style="text-align: right;">Dry time at 20°C</td> <td>At the touch about 6-8 hours; sandable after 24 hours</td> </tr> <tr> <td style="text-align: right;">Dilution</td> <td>BASE R: water</td> </tr> </table>	Color	White + Color samples	Appearance	Creamy	Packaging	BASE R: 4L-2,5L-0,750L CARRARA: 20KG-5KG GALLIPOLI FINO: 1,25KG PORTOFINO FINO: 1,25KG NAPOLI LUX: 1KG	Vehicle type	Vinyl acetate / vinyl-versed	Yield	BASE R: 6-8 sqm/Kg CARRARA: 2-2,5 sqm/Kg GALLIPOLI FINO: 10 sqm/Kg PORTOFINO FINO: 10 sqm/Kg NAPOLI LUX: 10 sqm/Kg	ph	8 +/- 0,5	Dry time at 20°C	At the touch about 6-8 hours; sandable after 24 hours	Dilution	BASE R: water
Color	White + Color samples																
Appearance	Creamy																
Packaging	BASE R: 4L-2,5L-0,750L CARRARA: 20KG-5KG GALLIPOLI FINO: 1,25KG PORTOFINO FINO: 1,25KG NAPOLI LUX: 1KG																
Vehicle type	Vinyl acetate / vinyl-versed																
Yield	BASE R: 6-8 sqm/Kg CARRARA: 2-2,5 sqm/Kg GALLIPOLI FINO: 10 sqm/Kg PORTOFINO FINO: 10 sqm/Kg NAPOLI LUX: 10 sqm/Kg																
ph	8 +/- 0,5																
Dry time at 20°C	At the touch about 6-8 hours; sandable after 24 hours																
Dilution	BASE R: water																

		CARRARA: ready to use GALLIPOLI FINO: ready to use PORTOFINO FINO: ready to use NAPOLI LUX: ready to use With water
	Clean up tools	
V.O.C. Content	CAT. A/I decorative paints Limit value EU (Dir. 2004/42/EC): from 2010=200 g/L CARRARA: less than 200 g/L Colorants: VOC FREE	
Limitations	<p>Recommended not to apply the product at temperatures below +5 ° C or above +40 ° C and relative humidity above 75%. Use the product on clean and dry surfaces. When using the product we always advice to wear properly safety equipment (e.g. mask, goggles and gloves. In case of contact with eyes, rinse with clean water and seek medical advice if irritation persist. Keep the product away from frost and excessive heat. Application on surfaces with salt efflorescence or subject to rising damp does not guarantee a perfect adhesion of the coating, it is necessary to restore the previously surface. Avoid application in direct sunlight. It is recommended finally, wash hands, tools and equipment immediately after use with hot water. Stability in the original unopened containers: 12 months</p>	

The technical informations herein are provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the Company may not be held liable for the results obtained using these product, as application conditions are beyond its control.

Industria Colori
duriplastic s.r.l.

73015 Salice Salentino (Lecce)
Tel. +39 0832 731840 Fax +39 0832 733841
www.duriplastic.com
www.italyacolour.com